

Agitator Rage

Unleash the most powerful Agitator ever engineered.

This isn't an upgrade – **it's a revolution.**

Agitator™ Rage delivers raw, on-demand force that dwarfs anything else on the market. Purpose-built for extreme drilling conditions, it hits harder, performs longer, and cuts friction like nothing you've seen before.

Powered by the legacy of 10,000+ successful Agitator On-Demand runs, Rage puts aggressive, high-impact energy directly in your control.

When drilling gets tough, this is the hammer you want in your string. No fluff. No compromise. Just brute-force performance engineered for the world's toughest wells.

Features and Benefits

- **Instant Power:** Single-dart activation for precise, on-demand force.
- **Extreme Output:** Increased pressure drop drives unmatched axial force and friction reduction energy.
- **Built to Last:** Rugged design thrives in the harshest wells.
- **Outperforms Competitors:** Excels in curves, long laterals, and tough runs.



Technical Data

| | | | |
|--------------------------------------|-----------------|-----------------|-----------------|
| Nominal size | 133 mm | 165 mm | 178 mm |
| True OD | 133 mm | 165 mm | 178 mm |
| Overall length | 4.11 m | 4.36 m | 4.30 m |
| Weight | 319 kg | 526 kg | 578 kg |
| Flow rate range | 755-1,705 LPM | 1,515-2,840 LPM | 1,705-3,405 LPM |
| Pressure drop (not activated) | 345-690 kPa | 345-690 kPa | 345-690 kPa |
| Pressure drop (activated) | 4,830-5,860 kPa | 4,830-8,270 kPa | 4,830-8,270 kPa |
| Tensile yield | 207,000 daN | 351,500 daN | 362,500 daN |
| Torsional yield | 42,710 Nm | 80,260 Nm | 88,130 Nm |
| Max temperature* | 160°C | 160°C | 160°C |

* High temperature option available on request (rated up to 190°C)